



MANY OPTIONS WITH INTERNAL 26=45 (AND/OR EXTERNAL MOTORS AND ENERGY STORAGE
 13B GROUND REFERENCE OR SUPPORT OR COUPLING i.e CARRIER 22 TO BOTH ENDS
 SUPPORTED FROM ONE END ONLY FOR ONE WAY CONTROL 47





Fig. 1

2/8



3/8




Fig. 3

4/8

LIKE RIDING A MOTORCYCLE
ANY MOBILE ON LAND, SEA OR AIR-CAN PROVIDE
PASSENGERS OR CARGO
THIS TILTING CAN BE DONE WITHOUT THE GEAR, HOWEVER
THE DOUBLE CONTRAROTATION CAN PROVIDE CONTINUOUS
CORRECTION OR OTHER REACTIVE MOVEMENTS AS WELL





Fig. 4A

5/8

RATIOS CHOSEN TO MATCH THE FEEDBACK WITH THE
FORCE REQUIRED. ALSO THE BODY OF THE GEAR IS
NORMALLY FIXED. BUT IF ALLOWED TO IT COULD BE
ROTATED LIKE THIS - (EITHER WAY)



CAN ALSO BE COMBINED WITH FIG 5—
PAGE 2-4—(OR FIG 3—PAGE 3-8)
TO CORRECT CASTOR AS WELL

Fig. 4B

6/8




Fig. 5A




Fig. 5B

7/8




Fig. 6

8/8




Fig. 7




Fig. 8